

SLG Slide Gate Operator

When an extra measure of building or perimeter security is required, consider our line of industrial slide gate operators. Our field-proven gate operators are in use throughout the world and are engineered to give many years of reliable service.

- **Printed circuit board design**
- **Heavy gauge welded steel cabinet with weather-tight gasket around the door and output drive shaft**
- **Double-grooved machined steel motor pulley with twin V-belt drive to input shaft**
- **Rotary type limits, ball bearing and permanently lubricated, with machined cams and spring-loaded retainers**
- **1" steel output shaft mounted in self-aligning pillow block bearings**
- **Emergency disconnect**



ACCESS TO PEACE OF MIND™

SECURITY • PARKING • ACCESS CONTROL

SLG



Specifications:

	Model	SLG12	SLG34	SLG1
Motor Hp		1/2 HP	3/4 HP	1 HP
Max. Gate Weight		900 lbs	1200 lbs	1500 lbs
Max. Opening Width	Cantilever	20 ft (6m)	26 ft (8m)	32 ft (10m)
	Roller	26 ft (8m)	36 ft (11m)	48 ft (15m)
	Overhead	36 ft (11m)	46 ft (14m)	58 ft (18m)
Max. Cycles Per Hour		40	30	20
Gate Travel Speed		50 ft/min (15 m/min)		
Shipping Weight		330 lbs (150 kg)		
Standard Voltages		120V or 240V Single Phase (other voltages, please specify)		

Right or left hand operation. Full motor overload protection.

Choice of Controls:

- Pushbutton Station
- Programmable Card Reader
- Telephone Entry
- Radio Control
- Key Switch
- Remote Custom Console
- Vehicle Loop Detector
- Heater

